

Hyosung is Revolutionizing the Self-Service Industry.

Being the ideal solution for off premise environments, the **MX5300SE** offers an advanced design and includes a user-friendly interface displayed on a 15" screen. This full Windows model can handle whatever transaction set you can dream up. It's sophisticated look combined with it's high cash capacity make the **MX5300SE** series a fantastic fit for both Retail and FI installs.

Features

Highest Availability

The **MX5300SE** is designed to provide reliability that is unequalled in the market, with minimum maintenance and maximum uptime.

High Capacity

The **MX5300SE** accommodates up to four 2,000 note cassettes for a maximum storage of 8,000 notes. The **MX5300SE** is an ideal solution for off premise environments.

Innovative Design

The **MX5300SE** features a user-friendly interface displayed on a vivid 15" screen.

Security Options

Hyosung ATMs defend against physical and logical attacks with a combination of multi-level anti-skimming, locked down operating system, white-listing, and encryption. The **MX5300SE** is also easily integrated with any monitoring solution to provide seamless data transfer for effective management.



HYOSUNG

MX5300SE

Specifications

Dimensions

- Height: 1397mm (55")
- Width: 460mm (18.1")
- Depth: 645mm (25.4")
- Weight: 280kg (617 lbs)

Environmental Conditions

- Temperature: 32°F – 104°F (0°C ~ 40°C)
- Humidity 25% – 85%

System Platform

- Microsoft Windows® CE 6.0

Customer Interface

- 15" TFT LCD screen
- Input type – 4x2 function key
- PIN Pad – PCI complaint
- ADA audio guidance – earphone jack
- Card Reader – DIP hybrid, EMV level 1, 2 compliant, anti-skimming

Media Handling

- Cash Dispenser
 - Up to 4 cassettes
 - 2,000 notes per cassette

Security

- Safe – UL291 business hours safe, level 1 safe
- Alarm – Seismic + heat
- Locking Device – Electronic safe lock, KABA mas cencon (optional)

Printer

- 3.1" graphical thermal receipt printer

Servicing

- Front Access
- State of health indicators for all modules

Power Supply

- AC 100V ~ 127V±10%, 200V ~ 240V±10% 50/60Hz

Additional Features

- Communication – TCP/IP

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.